

## SECTION 5

**Note!**

**Unless otherwise noted, listed Wheels and Brakes are FAA TSO C26 Approved.**

For a product to be TSO qualified, it has to have successfully demonstrated its ability to meet minimum performance standards in accordance with FAA recognized rating methods. The TSO approval of a product does not constitute installation approval or applicability on an FAA Type Certificated Aircraft. It is the responsibility of those installing these products to determine that the aircraft installation and its wheel and brake performance requirements are compatible for the TSO ratings of the wheel and brake. TSO approved products must have separate approval for installation in a FAA type certificated aircraft. TSO Approved Products may be installed only if performed under Title 14 CFR Part 43 or the applicable airworthiness requirements.

21-100D (40-2).....	5-10	40-59D.....	5-44	40-78A.....	5-33
27-100D (40-1).....	5-35	40-59E.....	5-44	40-78B.....	5-33
3040 (40-6).....	5-38	40-60.....	5-45	40-78E.....	5-33
3050 (40-7).....	5-38	40-60A.....	5-45	40-78J.....	5-33
3050A (40-7A).....	5-38	40-61.....	5-43	40-79A.....	5-48
3070 (40-5).....	5-36	40-66.....	5-43	40-83.....	5-48
3080A (40-3).....	5-36	40-67.....	5-39	40-83A.....	5-48
3080B (40-4).....	5-37	40-74.....	5-46	40-83B.....	5-48
3080D (40-116).....	5-37	40-74A.....	5-46	40-84.....	5-48
38501 (40-8).....	5-17	40-74B.....	5-46	40-84A.....	5-48
40-12.....	5-33	40-75B.....	5-47	40-84B.....	5-48
40-12A.....	5-33	40-75D.....	5-47	40-86.....	5-49
40-18.....	5-10	40-75E.....	5-47	40-86A.....	5-49
40-19.....	5-34	40-75F.....	5-47	40-86B.....	5-49
40-19A.....	5-34	40-75G.....	5-47	40-86E.....	5-49
40-21.....	5-39	40-75H.....	5-47	40-86F.....	5-49
40-24.....	5-39	40-75J.....	5-47	40-87.....	5-11
40-28.....	5-39	40-75P.....	5-47	40-87A.....	5-11
40-28D.....	5-39	40-75S.....	5-47	40-87C.....	5-11
40-30A.....	5-17	40-75T.....	5-47	40-87D.....	5-11
40-32.....	5-35	40-75W.....	5-47	40-87F.....	5-11
40-33.....	5-10	40-75Z.....	5-47	40-87G.....	5-11
40-34.....	5-40	40-76A.....	5-17	40-88C.....	5-49
40-37.....	5-43	40-76B.....	5-17	40-90.....	5-50
40-40A.....	5-71	40-76C.....	5-17	40-90A.....	5-50
40-40B.....	5-71	40-76D.....	5-18	40-90B.....	5-50
40-40C.....	5-71	40-76E.....	5-18	40-90D.....	5-50
40-40D.....	5-72	40-76F.....	5-18	40-90E.....	5-50
40-41.....	5-49	40-76G.....	5-18	40-90F.....	5-50
40-46.....	5-90	40-76H.....	5-18	40-96A.....	5-51
40-47.....	5-62	40-76P.....	5-17	40-96E.....	5-51
40-50.....	5-6	40-76-1.....	5-4	40-97A.....	5-52
40-55.....	5-17	40-77.....	5-11	40-97B.....	5-52
40-56.....	5-18	40-77A.....	5-11	40-97C.....	5-52
40-56B.....	5-18	40-77B.....	5-11	40-97D.....	5-52
40-56C.....	5-19	40-77C.....	5-12	40-97E.....	5-52
40-57.....	5-43	40-77D.....	5-12	40-97F.....	5-52
40-57A.....	5-43	40-77E.....	5-12	40-98.....	5-63
40-58.....	5-40	40-77F.....	5-12	40-98A.....	5-63
40-59.....	5-44	40-77G.....	5-11	40-98D.....	5-63
40-59A.....	5-44	40-78.....	5-33	40-98E.....	5-63

# Cleveland

Wheels &amp; Brakes



## McCauley Product Line